

Collection Oslo | Home & Contract

Oslo FR

Technical sheet

Composition:	100% Polyester		
Weight (m2):	380 g/m2		
Width:	140 cm		
Tear strength:	Warp: 110N Weft: 71N		
Seam slippage:	Warp: 2	Weft: 2	
Color fastness strength:	Dry: 4-5	Wet: 4-5	
Tensile strength:	Warp: 1200N	Weft: 590N	
Abrasion resistance:	> 40.000 cycles		
Color fastness to light:	5		
Pilling resistance:	4		
Fire retardant:	BS5852: Part 1: 1979, source 0 (cigarette)		

Notes:

Due to the manufacturing process, there may be differences in color tone between different batches.

Cleaning instructions:



Hand wash



Do not
bleach



Do not tumble
dry



Do not dry
clean



Do not iron



Dry flat

The technology of these fabrics improves some advanced properties:

- Easy cleaning with water
- Limited absorption of fluids
- High resistance to mechanical damage, such as scratches, snags
- Protection against viruses, bacteria and fungi

Thanks to this technology, these fabrics are able to overcome the challenges of everyday life, giving users maximum comfort and safety on a daily basis.



Easy Water Cleaning

At the production stage, fibers are coated with special molecules that protect the fabric from dirt. Thanks to this, all stains are quickly and efficiently cleaned.



Water Repellent

A technology of covering the fabric with a special hydrophobic coating that effectively hinders the absorption of spilled liquids, leaving drops on the surface of the material.



Fire Retardant

BS 5852: Part 1: 1979, Source 0 (Cigarette)



Notes:

Color shades may slightly vary from dye-lot to dye-lot.

The information in the Technical Sheet is provided by the manufacturer.

For more information visit mjcampos.com or contact us by email.